



## Specialty Engineered Materials Wire & Cable

Avient is here to help you consistently meet your flame retardant wire & cable product specification challenges head on. When you need consistency in processability or to meet your flame test performance requirements, we can help get you there. With on-time delivery as a standard and additional technical assistance when needed, Avient experts can provide support in selecting the best material for your application.

**APPLICATIONS:** Power cables, Ethernet category cables, industrial cables, solar installation cables, coaxial cables, fiber optics, hybrid cables

### SYNCURE™

Cross-Linked Polyethylene for Power Cable Insulation

- Resistant to heat, oil, creep and abrasion
- Fast extrusion speeds
- UL 44 & UL 4703 flame performance
- UL/CSA bulletins

### MAXXAM™ FR W&C

Flame Retardant Polypropylene for Category Cable Insulation and Cross-Webs

- Alternative to FEP
- Low dielectric
- Thin wall extrusion capabilities
- UL 444 & plenum yellow card flame performance

### FIRECON™

Flame Retardant Chlorinated Polyethylene for Industrial Cable Jackets

- Resistance to harsh environments
- Low temperature properties
- UV resistance
- UL 44 flame performance

### ECCOH™ LSFOH

Low Smoke and Fume, Non-Halogen for Insulation and Jackets

- Low smoke and toxicity
- Improved fire safety
- Resistance to chemicals
- UL44 and CPR flame performance

### ADDITIONAL SOLUTIONS

#### MAXXAM™ SY

Foamed Polypropylene for Coaxial Cable Insulation

#### SYNPRENE™

Flame Retardant Thermoplastic Elastomers

#### POLYMIX™

Customer Proprietary Formulations

For more information, please visit [avient.com](http://avient.com)  
or call +1.844.4AVIENT (+1.844.428.4368).

[www.avient.com](http://www.avient.com)



Copyright © 2020, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as “typical” or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient’s products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.