# COLOR AND ADDITIVE CONCENTRATES FOR WIRE AND CABLE



As a leading supplier to the wire and cable industry, we offer a broad portfolio that includes colorants and additives for various standards, applications, and polymer systems. A wide range of stock colors is readily available while an expansive selection of additives serves to enhance product performance. Custom formulations to meet specific requirements can be developed upon request.

# **ONCOLOR<sup>™</sup> COLOR CONCENTRATES**

- Complete range of in-stock color solutions designed specifically for telecommunications, energy, and automotive applications
  - Complete Munsell color range for telecommunications applications
  - Complete NEMA color range for electrical applications
  - J1128 SAE specifications for automotive applications
  - UL 2885 file E482856 for halogen-free formulations
- Custom color solutions for your most demanding low smoke, non-halogenated, UV, temperature, aging, and shrinkage requirements
- Weatherable pigments providing color fade resistance for demanding outdoor applications
- Optimized formulations for cross-linked polyethylene wire and cable constructions

### CESA<sup>™</sup> PERFORMANCE ADDITIVE CONCENTRATES

Custom designed additive solutions for your specific applications, providing added value through ease of processing, product performance, and operational cost savings

- **Laser marking** improve marking reliability and durability in all types of cable jacketing and insulating materials
- Antimicrobial help protect cables from harmful mold and bacteria growth
- Nucleating agents maintain critical dimensions and manage shrink characteristics
- Chemical foaming agents take out weight and reduce resin costs
- **UV stabilizers** protect resin material and extend product life
- Antioxidants maintain physical properties
- **Processing aids** minimize die drool associated with some materials

# COLORANT CHROMATICS<sup>™</sup> HIGH-TEMPERATURE POLYMER SOLUTIONS

- Fluoropolymer and high-temperature thermoplastics-based colorant and additive concentrates and compounds
- Dispersed pigments for coloring PTFE
- Functional additives including laser marking, foaming agents, and conductive, antistatic, radiopaque, reinforced, and cross-linked grades
- Full range of printing, striping, and marking inks



# **ONCOLOR<sup>™</sup> SOLUTIONS FOR TELECOMMUNICATIONS**

- PVC colorants designed for telecommunications and fiber optic applications
- PE colorants that are excellent for foam skin and solid insulation applications
- EVA colorants designed for cross-linked materials and resin applications including XLPE, XLPO, PVC, PE, and more

	PRODUCT CODE	LET DOWN RATIO	COLOR (Munsell)	_		PRODUCT CODE	LET DOWN RATIO	COLOR (Munsell)
	CC0000001	1.00%	Black			CC10225921	1.00%	Black
	CC00012837	1.00%	White			CC00012573	1.00%	White
	CC10225296	1.00%	Red			CC10222359	1.00%	Red
	CC10225298	1.00%	Gray			CC10223395	1.00%	Gray
	CC10225300	1.00%	Green				CC10222361	1.00%
ш	CC10225295	1.00%	Blue		PVC	CC00012376	1.00%	Blue
Δ.	CC10225297	1.00%	Orange		đ	CC10222363	1.00%	Orange
	CC10225299	1.00%	Yellow			CC10222360	1.00%	Yellow
	CC10225301	1.00%	Brown			CC10223394	1.00%	Brown
	CC10225603	1.00%	Purple			CC00012516	1.00%	Purple
	CC10225293	1.00%	Aqua			CC10062368	1.00%	Aqua
	CC10225294	1.00%	Pink			CC10223396	1.00%	Pink

	PRODUCT CODE	LET DOWN RATIO	COLOR (Munsell)
	CC10190635	3.00%	Black
	CC10190642	3.00%	White
	CC10190641	3.00%	Red
	CC10190637	3.00%	Gray
	CC10190638	3.00%	Green
	CC10185195	3.00%	Blue
	CC10185197	3.00%	Orange
	CC10190643	3.00%	Yellow
	CC10190636	3.00%	Brown
	CC10190640	3.00%	Purple
	CC10190634	3.00%	Aqua
	CC10190639	3.00%	Pink

	PRODUCT CODE	LET DOWN RATIO	COLOR (Munsell)
	CC10246438WE	2.00%	Aqua
	CC10245005WE	2.00%	Black
	CC10246090WE	2.00%	Blue
	CC10264438DR	2.00%	Brown
Ь	CC10245008WE	2.00%	Gray
800	CC10246092WE	2.00%	Green
UL 2885	CC10264439DR	3.00%	Orange
	CC10261866DR	2.00%	Pink
	CC10261867DR	2.00%	Purple
	CC10264436DR	2.00%	Red
	CC10245006WE	2.00%	White
	CC10246093WE	2.00%	Yellow

	PRODUCT CODE	LET DOWN RATIO	COLOR (Munsell)
	CC00012853	1.00%	Black
	CC00012946	1.00%	White
	CC10221766	1.00%	Red
	CC10221760	1.00%	Gray
	CC10221765	1.00%	Dk Green
	CC10221764	1.00%	Lt Green
EVA	CC10221757	1.00%	Dk Blue
ш	CC10221761	1.00%	Lt Blue
	CC10221767	1.00%	Orange
	CC10221763	1.00%	Yellow
	CC10221758	1.00%	Brown
	CC10221762	1.00%	Purple
	CC10224626	1.00%	Tan
	CC10221759	1.00%	Pink



# **ONCOLOR<sup>™</sup> SOLUTIONS FOR ENERGY CABLE APPLICATIONS**

• Recommended use rate may vary depending on specific application, process, equipment, and resin grade

	PRODUCT CODE	LET DOWN RATIO	COLOR (NEMA)
	CC00012342	1.00%	Black
	CC00012575	1.00%	White
	CC00012547	1.00%	Red
	CC10018221	1.00%	Gray
	CC00012444	1.00%	Dk Green
	CC10018222	1.00%	Lt Green
PVC	CC00012408	1.00%	Dk Blue
٩	CC00012407	1.00%	Lt Blue
	CC10013140	1.00%	Orange
	CC00036502	1.00%	Yellow
	CC00012363	1.00%	Dk Brown
	CC00012373	1.00%	Lt Brown
	CC00012526	1.00%	Purple
	CC10018225	1.00%	Tan

	PRODUCT CODE	LET DOWN RATIO	COLOR (NEMA)
	AB13820380	3.00%	Yellow
	AB24820333	3.00%	Orange
	AB32820571	3.00%	Pink
	AB33820570	3.00%	Red
Z	AB44820167	3.00%	Purple
ΝΟΊΛΝ	AB54820507	3.00%	Dark Blue
ź	AB63820502	3.00%	Dark Green
	AB72820811	3.00%	Gray
	AB84820533	3.00%	Brown
	AB94820333	3.00%	Black
	CC00016954	1.00%	White

# **ONCOLOR<sup>™</sup> SOLUTIONS FOR AUTOMOTIVE APPLICATIONS**

- EVA colorants designed for use with cross-linked materials such as XLPE
- Recommended use rate is 1.00% and may vary depending on specific application, process, equipment, and resin grade

	PRODUCT CODE	LET DOWN RATIO	COLOR		PRODUCT CODE	LET DOWN RATIO	COLOR
	CC00012853	1.00%	Black		CC00012342	1.00%	Black
	CC00012946	1.00%	White		CC00012575	1.00%	White
	CC10221766	1.00%	Red		CC00012535	1.00%	Red
	CC10221760	1.00%	Gray	28	CC00012461	1.00%	Gray
	CC10221765	1.00%	Dk Green		CC00012425	1.00%	Dk Green
EVA, J1128	CC10221764	1.00%	Lt Green		CC00012426	1.00%	Lt Green
	CC10221757	1.00%	Dk Blue	Ξ	CC00012379	1.00%	Dk Blue
	CC10221761	1.00%	Lt Blue		CC00012378	1.00%	Lt Blue
	CC10221767	1.00%	Orange	DVC	CC00012490	1.00%	Orange
	CC10221763	1.00%	Yellow		CC00012585	1.00%	Yellow
	CC10221758	1.00%	Brown		CC00012363	1.00%	Brown
	CC10221762	1.00%	Purple		CC00012525	1.00%	Purple
	CC10224626	1.00%	Tan		CC00012561	1.00%	Tan
	CC10221759	1.00%	Pink		CC00012507	1.00%	Pink

# A RANGE OF WORLD-CLASS SERVICES

With manufacturing facilities and innovation centers across the globe, we work with you to understand your goals and provide the expertise you need for your wire and cable applications.

#### LOOK TO US FOR SUPPORT WITH:

#### **Testing and Validation**

Fully accredited, in-house testing capabilities to generate data for insight into material behavior, environmental effects, and more

#### **Regulatory Coordination**

Dedicated product stewardship team assisting with new product approvals to reduce regulatory overhead and minimize risk

#### **Application Development Technical Service**

Technical experts specifically trained to work directly with your team in solving definitive application challenges

#### **Field Technical Service**

Onsite support for tool design, startup, and production optimization to gain manufacturing efficiencies and resolve technical issues

#### **Color and Additive Design Services**

Trend and color insights, and product development assistance to optimize design and gain speed to market

#### **Sustainability**

Innovative materials and solutions to help you meet your sustainability goals

1.844.4AVIENT www.avient.com



Copyright © 2024, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT Departe as particular, recommendation, or inducement to practice any patented invention without permission of the patent owner.