



Maxxam™ LO - Low Odor Talc-Filled Polypropylene for Underhood Automotive HVAC Uses

The Maxxam™ LO product line is a suite of olefin grades designed to meet the most stringent odor requirements in automotive HVAC applications, all without compromising performance or aesthetics.

With Maxxam LO, molders and OEM's can embrace the evolving Vehicle Interior Air Quality (VIAQ) regulatory environment, and add tangible value for the end-consumer by enabling a more natural smelling interior cabin, free of unpleasant odors.

Using its formulation expertise, PolyOne can also customize Maxxam LO grades to achieve a breadth of physical and mechanical properties that meet the specifications of any automotive OEM.

PolyOne's global reach allows our customers the ability to achieve greater product consistency wherever they manufacture in the world.

KEY CHARACTERISTICS

- Consistently achieves 3.0 per VDA 270
- Reduces VOC and emissions
- Inherent heat stabilization
- Customized physical property balance
- Customized process flexibility
- Natural, black, & custom colors possible

TYPICAL USES

PolyOne has designed Maxxam LO material for use in underhood automotive HVAC applications, including:

- Housings
- Ducts
- Fasteners/connectors
- Structural brackets

www.polyone.com

PolyOne™

Copyright © 2018, PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.